

High Pressure Cleaner

HSC1240 FR ÖL

NEW!



INOX



Anti Freeze circulatory system

Type	HSC1240 FR Oil		HSC1240-INOX FR Oil
Voltage	3/N/PE/AC/50Hz/400V		
Operating pressure	30-160bar/3-16MPa		
Max. pressure	180bar/18MPa		
Discharge capacity	300-1200l/h		
Nozzle size	070		
Hot water capacity	30-98°C		
Pump speed	1400rpm		
Connected load	7,6kW/14,1A		
Electrical protection	3x16A slow		
Weight net/with package	301kg/318kg		300kg/317kg
Dimensions device/with package (LxWxH)	122x75,5x162,5cm/125x81,5x175,5cm		122x75,5x162,5cm/125x81,5x175,5cm

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, thermostatically and SPS controlled frost protection circuit system with frost protection water recirculation in the internal WAB 40ltr, reliable down to -15°C outside temperature, stainless steel hot water boiler 65l capacity with preheating and buffering for immediate hot water use and hot water preparation in stand-by mode, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, total-switch-off after 5min, OPH-counter with service information, optical flame monitoring with photoelectric cell and fault indicator-light) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, integrated diesel-tank 60l, separate space for 2 x 20l cleaning detergent-container c/w Remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. Pump, heating and detergent, 7,5m connection cable.

Art.No.	528002	528001
----------------	--------	--------