

COLD WATER | MOBILE | SERIES 3x3

High Pressure Cleaner

KD1040



















KD1040-Premium





туре		KD1040-Standard	KD1040-Premium
Voltage Operating pressure Max. pressure Discharge capacity Nozzle size Max. Inlet temperature Pump speed Connected load Electrical protection	3/PE/AC/50Hz/400V 30-250bar/3-25MPa 270bar/27MPa 300-1000I/h 045 45°C 1400rpm 7,4kW/13,1A 3x16A slow	 10m HP-Hose DN06 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	 Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm

KD1040-Standard

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, ergonomic drawbar.

Art.No.	564000	564001
---------	--------	--------

Type