



## **High Pressure Cleaner**

**KDB1240** 



19



Туре			KDB1240-Standard		KDB1240-Premium
Engine Operating pressure Max. pressure Discharge capacity Nozzle size Max. Inlet temperature Pump speed Connected load Electric-Starter	Gasoline 30-180bar/3-18MPa 200bar/20MPa 300-1000l/h 055 45°C 1400rpm 13h.p. Honda Option	•	10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Detergent-Supply c/w Low-Pressure Injector and Metering-valve	•	Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Detergent-Supply c/w Low-Pressure Injector and Metering-valve
Weight net/with package			94kg/107kg		102kg/115kg
Dimensions device/with package (LxWxH)			100x74x77cm/120x80x90cm		100x74x97cm/120x80x125cm

Robust, corrosion-resistant, self-supporting device chassis, with tilt-proof equipment buggy, made of robust steel pipe galvanized and powder-coated, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, gearbox for reducing the high-pressure pump speed, 2-fold safety system, unloader safety-valve c/w Infinitely variable pressure and quantity regulation and safety-valve, automatic load-idle speed control, 4 large ruber-pneumatic tires for rough terrain, with a patented wheel brake, external detergent supply.

Art.No.	168001	168002
Art.No. device with electric-starter	169001	169002