

COLD WATER | STATIONARY | SERIES KS High Pressure Cleaner



Hot water resistant







| Туре | | | KS1140 | KS1140-INOX |
|--|--|---|--|--|
| Voltage Operating pressure Max. pressure Discharge capacity Nozzle size Max. Inlet temperature Pump speed Connected load Electrical protection | 3/N/PE/AC/50Hz/400V 30-170bar/3-17MPa 190bar/19MPa 300-1000l/h 055 80°C 1400rpm 6,5kW/10A 3x16A slow | • | 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° 4I Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve | Stainless Steel (Food-Safe) 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° 4I Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve |
| Weight net/with package | | | 120kg/135kg | 120kg/135kg |
| Dimensions device/with package (LxWxH) | | | 102x50x50cm/119x88x127cm | 102x50x50cm/119x88x127cm |

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless- steel), wall-bracket, opening of the device hood by supporting gas pressure springs, triplex-piston pump with brass pump head, hot-water resistant up to 80°C, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min with leakage-recognition, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, robust rotary on-off switch, 7,5m connection cable.