


## HOT WATER | MOBILE | OIL HEATED | SERIES ETRONIC II

## **High Pressure Cleaner**

HD1240







Туре		HD1240-Standard	HD1240-Premium
Voltage Operating pressure Max. pressure Discharge capacity Nozzle size Hot water capacity Pump speed Connected load Electrical protection	3/PE/AC/50Hz/400V 30-160bar/3-16MPa 180bar/18MPa 300-1200l/h 070 30-98°C (150°C) 1400rpm 7,6kW/11,5A 3x16A slow	<ul> <li>Etronic II - Controls</li> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25<sup>c</sup></li> <li>Water-Supply separation acc.</li> <li>Chemical supply in high-press Metering-valve</li> </ul>	<ul> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> </ul>
Weight net/with package		177kg/206kg	186kg/218kg
Dimensions device/with package (LxWxH)		107x73,5x102cm/119x88x1	27cm 107x73,5x102cm/119x88x127cm

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (Start-stop system with switch-off delay, total-switch-off after 20min, OPH-counter with service information, low-water cut-off, low-fuel cut-off, optical flame monitoring with photoelectric cell and fault indicator-light, steam-stage) 2 motors system (independent of the direction of rotation) separately for H.P.Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, integrated diesel-tank 25l, integrated detergent-tank 20l, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

Art.No.