

HOT WATER | MOBILE | OIL HEATED | SERIES ETRONIC II

## High Pressure Cleaner

**HD823** 

**Type** 

Dimensions device/with package (LxWxH)





1400 U/min
























**HD823-Premium** 

107x73,5x102cm/119x88x127cm

| Voltage                 | 1/N/PE/AC/50Hz/230V | Etronic II - Controls   | Etronic II - Controls  |
|-------------------------|---------------------|---|--|
| Operating pressure      | 30-140bar/3-14MPa   | <ul> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w         Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w         Metering-valve</li> </ul> | <ul> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w<br/>Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>Water-Supply separation acc.<br/>DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w<br/>Metering-valve</li> </ul> |
| Max. pressure           | 160bar/16MPa        |   |  |
| Discharge capacity      | 300-720l/h          |   |  |
| Nozzle size             | 045                 |   |  |
| Hot water capacity      | 30-98°C (150°C)     |   |  |
| Pump speed              | 1400rpm             |   |  |
| Connected load          | 3,4kW/15A           |   |  |
| Electrical protection   | 16A slow            |   |  |
| Weight net/with package |                     | 158kg/186kg   | 167kg/195kg  |

HD823-Standard

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (Start-stop system with switch-off delay, total-switch-off after 20min OPH-counter with service information, low-water cut-off, low-fuel cut-off, optical flame monitoring with photoelectric cell and fault indicator-light, steam-stage) 2 motors system (independent of the direction of rotation) separately for H.P.Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, integrated diesel-tank 25l, integrated detergent-tank 20l, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

107x73,5x102cm/119x88x127cm

| Art.No. | 496001 | 496002 |
|---------|--------|--------|
|---------|--------|--------|