


## HOT WATER | MOBILE | ELECTRIC HEATED | SERIES HDE

## High Pressure Cleaner

HDE840 12kW





Туре		HDE840 12kW-Standard	HDE840 12kW-Premium
Voltage Operating pressure Max. pressure Discharge capacity Nozzle size Heating capacity Hot water capacity Pump speed Connected load Electrical protection	3/N/PE/AC/50Hz/400V         30-140bar/3-14MPa         160bar/16MPa         300-720l/h         045         12kW         30-80°C         1400rpm         16,8kW/26,2A         3x32A slow	<ul> <li>Etronic I - Controls</li> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	<ul> <li>Etronic I - Controls</li> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Weight net/with package		119kg/140kg	128kg/149kg
Dimensions device/with package (LxWxH)		107x73,5x102cm/119x88x127cm	107x73,5x102cm/119x88x127cm

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, stainless-steel hotwater-boiler with 65I capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation, triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic I - controls: (start-stop system with switch-off delay, stand-by system for heating, low-water cut-off), unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, 2 integrated detergent-tank with 20I capacity, 2-stage rotary on-off switch with stand-by function, 7,5m connection cable, removable ergonomic drawbar.

106002