

HOT WATER | STATIONARY | OIL HEATED | SERIES HSC

## High Pressure Cleaner

**HSC823** 







1400 U/min

















Туре		HSC823		HSC823-INOX
Voltago	1/N/DE/AC/E0H=/220\/	Etronic II Controls	_	Stainless steel (food safe)

Voltage	1/N/PE/AC/50Hz/230V	Etronic II - Controls	Stainless steel (food safe)	
Operating pressure	30-140bar/3-14MPa	<ul> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	Etronic II - Controls	
Max. pressure	160bar/16MPa		<ul><li>10m HP-Hose DN08 - 315bar</li><li>Trigger-Gun with swivel</li></ul>	
Discharge capacity	300-720l/h		Spray-Lance 900mm c/w	
Nozzle size	045		Stainless-Steel Jet-Nozzle 25°	Nozzle-Protection
Hot water capacity	30-98°C		Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc.	
Pump speed	1400rpm		• Chemical supply in high-pressure Jet c/w DIN EN 1717 class	DIN EN 1717 class 4
Connected load	3,4kW/15A			Chemical supply in high-pressure Jet c/w
Electrical protection	16A slow		Metering-valve	
Weight net/with package		301kg/318kg	300kg/317kg	
Dimensions device/with package (LxWxH)		122x75.5x162.5cm/125x81.5x175.5cm	122x75.5x162.5cm/125x81.5x175.5cm	

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, total-switch-off after 20min, OPH-counter with service information, optical flame monitoring with photoelectric cell and fault indicator-light DIN EN 298) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, integrated diesel-tank 60l, seperatee space for 2 x 20l cleaning detergent-container c/w Remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. Pump, heating and detergent, 7,5m connection cable.

	Art.No.	52601	526010
--	---------	-------	--------