

## COLD WATER | MOBILE | GASOLINE POWERED | SERIES KDB

## **High Pressure Cleaner**

**KDB1540** 





Туре		KDB1540-Standard	KDB1540-Premium
Engine Operating pressure Max. pressure Discharge capacity Nozzle size Max. Inlet temperature Pump speed Connected load Electric-Starter	Gasoline 30-280bar/3-28MPa 300bar/30MPa 300-1000l/h 035 45°C 1400rpm 18h.p. B&S 2-Cylinder Option	<ul> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>	<ul> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>
Weight net/with package		96kg/103kg	111kg/124kg
Dimensions device/with package (LxWxH)		100x74x77cm/120x80x90cm	100x74x97cm/120x80x125cm

Robust, corrosion-resistant, self-supporting device chassis, with tilt-proof equipment buggy, made of robust steel pipe galvanized and powder-coated, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, gearbox for reducing the high-pressure pump speed, 2-fold safety system, unloader safety-valve c/w Infinitely variable pressure and quantity regulation and safety-valve, automatic load-idle speed control, 4 large ruber-pneumatic tires for rough terrain, with a patented wheel brake, external detergent supply.

Art.No.	170001	170002
Art.No. device with electric-starter	171001	171002