


# High Pressure Cleaner

**KDD1240**



**1400  
U/min**



Type		KDD1240-Standard	KDD1240-Premium
Engine	Diesel	<ul style="list-style-type: none"> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> <li>With electric starter</li> </ul>	<ul style="list-style-type: none"> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> <li>With electric starter</li> </ul>
Operating pressure	30-180bar/3-18MPa		
Max. pressure	200bar/20MPa		
Discharge capacity	300-1000l/h		
Nozzle size	050		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	10h.p. Diesel Yanmar		
Electric-Starter	Starter-Generator		
Weight net/with package		116kg/129kg	124kg/137kg
Dimensions device/with package (LxWxH)		100x74x77cm/120x80x90cm	100x74x97cm/120x80x125cm

Robust, corrosion-resistant, self-supporting device chassis, with tilt-proof equipment buggy, made of robust steel pipe galvanized and powder-coated, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, gearbox for reducing the high-pressure pump speed, 2-fold safety system, unloader safety-valve c/w Infinitely variable pressure and quantity regulation and safety-valve, automatic load-idle speed control, 4 large rubber-pneumatic tires for rough terrain, with a patented wheel brake, external detergent supply.

<b>Art.No.</b>	174001	174002
----------------	--------	--------