

HOT WATER | MOBILE | OIL HEATED | SERIES ETRONIC I

High Pressure Cleaner

HD623 UK





1400 U/min




















Туре		HD623 UK-Standard	HD623 UK-Premium
Voltage Operating pressure Max. pressure Discharge capacity Nozzle size Hot water capacity Pump speed Connected load Electrical protection	1/N/PE/AC/50Hz/240V 30-130bar/3-13MPa 160bar/16MPa 300-600l/h 040 30-98°C 1400rpm 3,1kW/12,7A 13A slow	 Etronic I - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	 Etronic I - Controls Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve
Weight net/with package		149kg/170kg	158kg/179kg
Dimensions device/with package (LxWxH)		107x73,5x102cm/119x88x127cm	107x73,5x102cm/119x88x127cm

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic I - controls: "Start-stop system with switch-off delay, total-switch-off after 20min" 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, integrated diesel-tank 25l, integrated detergent-tank 20l, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

Art.No.	497000	497003