


High Pressure Cleaner

HSC923 UK








**1400
U/min**


TSS


**TOTAL
STOP**











INOX

Type	HSC923 UK	HSC923 UK-INOX
Voltage	1/N/PE/AC/50Hz/240V	
Operating pressure	30-100bar/3-10MPa	
Max. pressure	120bar/12MPa	
Discharge capacity	300-840l/h	
Nozzle size	070	
Hot water capacity	30-98°C	
Pump speed	1400rpm	
Connected load	3,3kW/13A	
Electrical protection	13A slow	
Weight net/with package	301kg/318kg	300kg/317kg
Dimensions device/with package (LxWxH)	122x75,5x162,5cm/125x81,5x175,5cm	122x75,5x162,5cm/125x81,5x175,5cm
	<ul style="list-style-type: none"> Etronic II - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve 	<ul style="list-style-type: none"> Stainless steel (food safe) Etronic II - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve
Art.No.	534001	534002

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, total-switch-off after 20min, OPH-counter with service information, optical flame monitoring with photoelectric cell and fault indicator-light DIN EN 298) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, integrated diesel-tank 60l, separate space for 2 x 20l cleaning detergent-container c/w Remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. Pump, heating and detergent, 7,5m connection cable.