

COLD WATER | MOBILE | SERIES 2x2

High Pressure Cleaner

KD523 UK





1400 U/min













туре			KD523 UK-Standard		KD523 UK-Premium
Voltage	1/N/PE/AC/50Hz/240V	•	10m HP-Hose DN06 - 250bar	•	Hose-Reel
Operating pressure	30-140har/3-14MPa	•	Trigger-Gun with swivel	•	15m HP-Hose DN06 - 250bar

Voitage	1/14/1 1/1/12/2104	1011111111030 21000 230001	- Hose reel
Operating pressure	30-140bar/3-14MPa	 Trigger-Gun with swivel Spray-Lance 700mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	 15m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 700mm c/w Vario-Nozzle
Max. pressure	160bar/16MPa		
Discharge capacity	300-600l/h		Stainless-Steel Jet-Nozzle 25°
Nozzle size	043		Spray-Lance 900mm c/w Rotary-Nozzle
Max. Inlet temperature	45°C		Detergent-Supply c/w Low-Pressure Injector and Metering-valve
Pump speed	2800rpm		Injector and Metering-valve
Connected load	2,4kW/12A		
Electrical protection	13A slow		
Weight net/with package		37kg/41kg	44kg/48kg
Dimensions device/with package (LxWxH)		60x40x86cm/66x42x96cm	60x40x86cm/66x42x96cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable.

Art.No.	559003	559004
AI LINO:	333003	333001