

COLD WATER | MOTOR PUMP UNITS | SERIES MP High Pressure Cleaner



Hot water resistant









Туре			MP823 UK		Wall mounting		Wall mounting STR
Voltage	1/N/PE/AC/50Hz/230V	•	Delivery without Accessories	•	Delivery without	•	20m HP-Hose
Operating pressure	30-120bar/3-12MPa				Accessories		DN08 - 315bar
Max. pressure	140bar/14MPa					•	Hose reel
Discharge capacity	300-720l/h						
Nozzle size	050						
Max. Inlet temperature	80°C						
Pump speed	1400rpm						
Connected load	2,9kW/11,1A						
Electrical protection	16A slow						
Weight net/with package			-		-		-
Dimensions device/with package (LxWxH)		4	18x33,5x33,5cm/60x40x50cm		-		-

Motor-pump unit for OEM-use, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless- steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min with leakage-recognition, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, robust rotary on-off switch, 7,5m connection cable.

		Art.No.	234673	2980331	2980332
--	--	---------	--------	---------	---------