

Series KD4x4

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD1140



KD1140 Standard

Art. No. 551005



KD1140 Premium

Art. No. 551006



AREAS OF APPLICATION

Technical Data

| Type | KD1140-Standard | | KD1140-Premium | |
|---|-------------------|--|--|--|
| Voltage | 3/PE/AC/50Hz/400V | <ul style="list-style-type: none"> 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° 35l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve | <ul style="list-style-type: none"> Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 25l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve | |
| Operating pressure | 30-250bar/3-25MPa | | | |
| Max. pressure | 270bar/27MPa | | | |
| Discharge capacity | 300-1000l/h | | | |
| Nozzle size | 045 | | | |
| Max. Inlet temperature | 45°C | | | |
| Pump speed | 1400rpm | | | |
| Connected load | 7,4kW/13,1A | | | |
| Electrical protection | 3x16A slow | | | |
| Weight net/with package | | 89kg/113kg | 97kg/121kg | |
| Dimensions device/with package (LxWxH) | | 98x62x100cm/109x63x112cm | 98x62x100cm/109x63x112cm | |
| <p>Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.</p> | | | | |
| Art.No. | | 551005 | 551006 | |