

Series KD4x4

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD1140-Food



KD1140 Standard

Art. No. 561003

KD1140 Premium

Art. No. 561004



AREAS OF APPLICATION

Technical data

Type	KD1140-F-Standard		KD1140-F-Premium		
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> • 10m HP-Hose DN08 - 315bar blue • Trigger-Gun with swivel • Double Spray-Lance 900mm c/w Nozzle-Protection • Stainless-Steel Jet-Nozzle 25° • 35l Cleaning-Detergent tank • Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> • Hose-Reel • 20m HP-Hose DN08 - 315bar blue • Trigger-Gun with swivel • Double Spray-Lance 900mm c/w Nozzle-Protection • Stainless-Steel Jet-Nozzle 25° • SoftFoam Kit with 2l foam detergent tank • Spray-Lance 900mm c/w Rotary-Nozzle • 25l Water-Storage tank • Water-Supply separation acc. DIN EN 1717 class 4 • Chemical supply in high-pressure Jet c/w Metering-valve 		
Operating pressure	30-180bar/3-18MPa				
Max. pressure	200bar/20MPa				
Discharge capacity	300-1000l/h				
Nozzle size	055				
Max. Inlet temperature	S: 80°C				
Pump speed	1400rpm				
Connected load	6,9kW/12,5A				
Electrical protection	3x16A slow				
Weight net/with package					
Dimensions device/with package (LxWxH)		98x62x100cm/109x63x112cm	98x62x100cm/109x63x112cm		

Food progressing with abrasion resistant high pressure hose blue, self-supporting, robust, corrosion-free, rotation-moulded device-chassis for food industry, stainless steel, impact-resistant device-cover made of ABS, triplex-piston pump with chrome, nickel plated pump head (hot water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar stainless steel.

Art.No.	551003	551004
----------------	--------	--------