

Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD1240



KD1240 Standard

Art. No. 565000



KD1240 Premium

Art. No. 565001



AREAS OF APPLICATION

Technical Data

Type		KD1240-Standard	KD1240-Premium
Voltage	3/PE/AC/50Hz/400V	10m HP-Hose DN08 - 315bar - Trigger-Gun with swivel - Spray-Lance 900mm c/w Vario-Nozzle - Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank - Detergent-Supply c/w Low-Pressure Injector and Metering-valve	- Hose-Reel 20m HP-Hose DN08 - 315bar - Trigger-Gun with swivel - Spray-Lance 900mm c/w Nozzle-Protection - Stainless-Steel Jet-Nozzle 25° - Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank - Water-Supply separation acc. DIN EN 1717 class 4 - Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-170bar/3-17MPa		
Max. pressure	190bar/19MPa		
Discharge capacity	300-1300l/h		
Nozzle size	070		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	7,4kW/13,1A		
Electrical protection	3x16A slow		
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, ergonomic drawbar.

Art.No.	565000	565001
---------	--------	--------