

Series KD4x4

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD1340



KD1340 Standard

Art. No. 552003



KD1340 Premium

Art. No. 552004



AREAS OF APPLICATION

Technical Data

Type		KD1340-Standard	KD1340-Premium
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° 35l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Hose-Reel 20m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 25l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-170bar/3-17MPa		
Max. pressure	190bar/19MPa		
Discharge capacity	300-1300l/h		
Nozzle size	070		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	7,4kW/13,1A		
Electrical protection	3x16A slow		
Weight net/with package		89kg/113kg	97kg/121kg
Dimensions device/with package (LxWxH)		98x62x100cm/109x63x112cm	98x62x100cm/109x63x112cm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel-plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar.

Art.No.	552003	552004
----------------	--------	--------