

Series KD2x2

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD523 UK



KD523 UK Standard
Art. No. 559003



KD523 UK Premium
Art. No. 559004



AREAS OF APPLICATION

Technical Data

Type	KD523-UK Standard		KD523-UK Premium	
Voltage	1/N/PE/AC/50Hz/240V	<ul style="list-style-type: none"> 10m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 700mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Hose-Reel 15m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 700mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	
Operating pressure	30-140bar/3-14MPa			
Max. pressure	155bar/15,5MPa			
Discharge capacity	300-600l/h			
Nozzle size	043			
Max. Inlet temperature	45°C			
Pump speed	2800rpm			
Connected load	2,4kW/12A			
Electrical protection	13A slow			
Weight net/with package				37kg/41kg
Dimensions device/with package (LxWxH)		60x40x86cm/66x42x96cm	60x40x86cm/66x42x96cm	

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable.

Art.No.	559003	559004
----------------	--------	--------