

## Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

# KD623



**KD623 Standard**

Art. No. 558001



**KD623 Premium**

Art. No. 558002



AREAS OF APPLICATION

## Technical Data

Type	KD623-Standard		KD623-Premium		
Voltage	1/N/PE/AC/50Hz/230V	<ul style="list-style-type: none"> <li>10m HP-Hose DN06 - 250bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>17l Cleaning-Detergent tank</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>Hose-Reel</li> <li>15m HP-Hose DN06 - 250bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>15l Water-Storage tank</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>		
Operating pressure	30-160bar/3-16MPa				
Max. pressure	180bar/18MPa				
Discharge capacity	300-600l/h				
Nozzle size	035				
Max. Inlet temperature	45°C				
Pump speed	1400rpm				
Connected load	2,9kW/14,2A	42kg/66kg	48kg/72kg		
Electrical protection	16A slow	80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm		
Weight net/with package					
Dimensions device/with package (LxWxH)					

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.

<b>Art.No.</b>	<b>558001</b>	<b>558002</b>
----------------	---------------	---------------