

Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD623 UK



KD623 UK Standard

Art. No. 558003



KD623 UK Premium

Art. No. 558004



AREAS OF APPLICATION

Technical Data

| Type | KD623-UK Standard | | KD623-UK Premium | |
|--|---------------------|--|---|--|
| Voltage | 1/N/PE/AC/50Hz/240V | <ul style="list-style-type: none"> 10m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve | <ul style="list-style-type: none"> Hose-Reel 15m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve | |
| Operating pressure | 30-130bar/3-13MPa | | | |
| Max. pressure | 150bar/15MPa | | | |
| Discharge capacity | 300-600l/h | | | |
| Nozzle size | 040 | | | |
| Max. Inlet temperature | 45°C | | | |
| Pump speed | 1400rpm | | | |
| Connected load | 2,9kW/11,4A | | | |
| Electrical protection | 13A slow | | | |
| Weight net/with package | | 42kg/66kg | 48kg/72kg | |
| Dimensions device/with package (LxWxH) | | 80,5x48,5x95cm/109x63x104cm | 80,5x48,5x95cm/109x63x104cm | |

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.

| | | |
|----------------|---------------|---------------|
| Art.No. | 558003 | 558004 |
|----------------|---------------|---------------|