

Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

KD623



KD623 UK Standard

Art. No. 558003



KD623 UK Premium

Art. No. 558004



AREAS OF APPLICATION

Technical Data

Type	KD623-UK Standard		KD623-UK Premium	
Voltage	1/N/PE/AC/50Hz/240V	<ul style="list-style-type: none"> 10m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° 17l Cleaning-Detergent tank Detergent-Supply c/w Low-Pressure Injector and Metering-valve 	<ul style="list-style-type: none"> Hose-Reel 15m HP-Hose DN06 - 250bar Trigger-Gun with swivel Spray-Lance 900mm c/w Vario-Nozzle Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 15l Water-Storage tank Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve 	
Operating pressure	30-130bar/3-13MPa			
Max. pressure	150bar/15MPa			
Discharge capacity	300-600l/h			
Nozzle size	040			
Max. Inlet temperature	45°C			
Pump speed	1400rpm			
Connected load	2,9kW/11,4A			
Electrical protection	13A slow			
Weight net/with package		42kg/66kg	48kg/72kg	
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm	

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.

Art.No.	558003	558004
----------------	---------------	---------------