

## Series KD3x3

HIGH PRESSURE CLEANER | COLD WATER | MOBILE

# KD940



**KD940 Standard**

Art. No. 561001



**KD940 Premium**

Art. No. 561002



AREAS OF APPLICATION

## Technical Data

Type	KD940-Standard		KD940-Premium	
Voltage	3/PE/AC/50Hz/400V	<ul style="list-style-type: none"> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Vario-Nozzle</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>17l Cleaning-Detergent tank</li> <li>Detergent-Supply c/w Low-Pressure Injector and Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>Hose-Reel</li> <li>15m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>15l Water-Storage tank</li> <li>Water-Supply separation acc. DIN EN 1717 class 4</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	
Operating pressure	30-190bar/3-19MPa			
Max. pressure	210bar/21MPa			
Discharge capacity	300-840l/h			
Nozzle size	045			
Max. Inlet temperature	45°C			
Pump speed	1400rpm			
Connected load	5,2kW/9,1A			
Electrical protection	3x16A slow			
Weight net/with package				
Dimensions device/with package (LxWxH)		80,5x48,5x95cm/109x63x104cm	80,5x48,5x95cm/109x63x104cm	

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar.

Art.No.	561001	561002
---------	--------	--------