

Series KSM

HIGH PRESSURE CLEANER | COLD WATER | STATIONARY

KSM2740



KSM2740-INOX

Art. No. 156201



AREAS OF APPLICATION

Technical Data

Type		KSM2740-INOX
Voltage	3/N/PE/AC/50Hz/400V	- Stainless Steel (Food-Safe) 7" Touch-Screen Monitor - PLC Controls Siemens S7-1200 - Automatic Switch On and Off Control for high-pressure pumps - Automatic Stand-By Operation - Pressureless pipes in Stand-By - Booster-Supply-Pump 30,5l Water-Storage tank - Water-Supply separation acc. DIN EN 1717 class 4 - Maintenance interval display
Operating pressure	30-180bar/3-18MPa	
Max. pressure	200bar/20MPa	
Discharge capacity	900-2700l/h	
Nozzle size	3x050	
Max. Inlet temperature	80°C	
Pump speed	1400rpm	
Connected load	21,0kW/38A	
Electrical protection	3x50A slow	
Weight net/with package		395kg/430kg
Dimensions device/with package (LxWxH)		164,5x75,2x145,1/200x110x160cm

Self-supporting, robust, device-chassis made out of stainless-steel, suitable for floor installation, triplex-piston pump with chrome-nickel pump head, hot-water resistant up to 85°C, high-performance ceramic piston, stainless-steel valves, leakage-return, booster-pump for charging the high-pressure pumps (cavitation avoidance), automatic pump-on and shut-off control by plc with leakage-recognition, un-loader safety-valve for monitoring, pressureless pipe-system in stand-by mode, robust rotary on-off switch - lockable.

Art.No.	156201
---------	--------