Series KSM

HIGH PRESSURE CLEANER | COLD WATER | STATIONARY

KSM3640



KSM3640-**INOX**

Art. No. 156300

made by EHRLE
made in Germany

AREAS OF APPLICATION

Technical Data

Type	**KSM3640-INOX**
Voltage	3/N/PE/AC/50Hz/400V
Operating pressure	30-180bar/3-18MPa
Max. pressure	200bar/20MPa
Discharge capacity	900-3600l/h
Nozzle size	4x050
Max. Inlet temperature	80°C
Pump speed	1400rpm
Connected load	27,0kW/50A
Electrical protection	3x63A slow
Weight net/with package	-
Dimensions device/with package (LxWxH)	213x80x209cm/ -

- Stainless Steel (Food-Safe)
- 7" Touch-Screen Monitor
- PLC Controls Siemens S7-1200
- Automatic Switch On and Off Control for high-pressure pumps
- Automatic Stand-By Operation
- Pressureless pipes in Stand-By
- Booster-Supply-Pump
- 60l Water-Storage tank
- Water-Supply separation acc. DIN EN 1717 class 4
- Maintenance interval display

Self-supporting, robust, device-chassis made out of stainless-steel, suitable for floor installation, triplex-piston pump with chrome-nickel pump head, hot-water resistant up to 85°c, high-performance ceramic piston, stainless-steel valves, leakage-return, booster-pump for charging the high-pressure pumps (cavitation avoidance), automatic pump-on and shut-off control by plc with leakage-recognition, unloader safety-valve for monitoring, pressureless pipe-system in stand-by mode, robust rotary on-off switch - lockable.

Art.No.	156300