

# EHRLE Terminal-Serie



**WT WashTerminal DUO SV6 - Self-Service CarWash  
for 2-wash bays | Gas heated**

## Description:

- Self-service car wash with two wash bays
- Self-supporting stainless steel outdoor housing
- CC-talk electronic coin validator for cash and tokens
- Option for payment with carwash key or credit card system
- LED display for remaining amount of money
- Foam generator for Foam ActivePower Pearl MicroPowder
- Micro powder dosing system for ActivePower Pearl MicroPowder
- Liquid dosing for paint protection UltraProtection
- Liquid dosing for high gloss SuperFinish
- Ionic water softener 1x80m<sup>3</sup>/dH with salt tank
- Reverse osmosis 7.200l/da - for spotless drying results
- Osmosis water storage tank 400l with level control
- Frost protection device with internal frost protection WAB
- Y-Lance container SV6
- Heat-Exchanger with inline-pump for floor-heating 15kW (optional)

## Gas heated:

- Modulating stainless steel boiler
- Heating capacity 15-65kW
- Efficiency up to 108% in the condensate range
- Coaxial air/flue gas system (LAS), 1m

## Technical data

Technical data	WashTerminal SV6: Gas heated
Voltage	3/PE/AC/50Hz/400V
Operating pressure	130bar/13MPa
Max. Pressure	150bar/15MPa
Discharge Capacity	720l/h - 12l/min
Connected load	9,0kW
Electrical protection	3x20A träge
Dimension (with HD/SoftFoam Brush) LxWxH	120x208x248cm
Weight	xxx
Art. No.	<b>197003</b>

System variant SV6

**SV6**

Gas heated



## Application programmes

System variant: **with Foam Brush (SV6)**



EHRLE GmbH  
Industriestraße 3  
D-89165 Dietenheim



[www.ehrle.com](http://www.ehrle.com)



[info@ehrle.de](mailto:info@ehrle.de)



+49 7303 1600-0

