


# High Pressure Cleaner

## HSC1140








**1400  
U/min**


**TSS**


**TOTAL  
STOP**











INOX

Type	HSC1140		HSC1140-INOX
Voltage	3/N/PE/AC/50Hz/400V		Stainless steel (food safe)
Operating pressure	30-180bar/3-18MPa		Etronic II - Controls
Max. pressure	200bar/20MPa		10m HP-Hose DN08 - 315bar
Discharge capacity	300-1000l/h		Trigger-Gun with swivel
Nozzle size	055		Spray-Lance 900mm c/w Nozzle-Protection
Hot water capacity	30-98°C		Stainless-Steel Jet-Nozzle 25°
Pump speed	1400rpm		Water-Supply separation acc. DIN EN 1717 class 4
Connected load	6,5kW/12,2A		Chemical supply in high-pressure Jet c/w Metering-valve
Electrical protection	3x16A slow		
Weight net/with package	301kg/318kg		300kg/317kg
Dimensions device/with package (LxWxH)	122x75,5x162,5cm/125x81,5x175,5cm		122x75,5x162,5cm/125x81,5x175,5cm

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, total-switch-off after 20min, OPH-counter with service information, optical flame monitoring with photoelectric cell and fault indicator-light) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, integrated diesel-tank 60l, separate space for 2x20l cleaning detergent-container c/w Remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. Pump, heating and detergent, 7,5m connection cable.

Art.No.	52702	527
---------	-------	-----