

High Pressure Cleaner

HSC1140 FR OIL

NEW!




1400 U/min

TSS

TOTAL STOP







INOX



Anti Freeze circulatory system

| Type | HSC1140 FR Oil | | HSC1140-INOX FR Oil |
|--|-----------------------------------|--|-----------------------------------|
| Voltage | 3/N/PE/AC/50Hz/400V | | |
| Operating pressure | 30-180bar/3-18MPa | | |
| Max. pressure | 200bar/20MPa | | |
| Discharge capacity | 300-1000l/h | | |
| Nozzle size | 055 | | |
| Hot water capacity | 30-98°C | | |
| Pump speed | 1400rpm | | |
| Connected load | 7,5kW/13,7A | | |
| Electrical protection | 3x16A slow | | |
| Weight net/with package | 301kg/318kg | | 300kg/317kg |
| Dimensions device/with package (LxWxH) | 122x75,5x162,5cm/125x81,5x175,5cm | | 122x75,5x162,5cm/125x81,5x175,5cm |

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, thermostatically and SPS controlled frost protection circuit system with frost protection water recirculation in the internal WAB 40ltr, reliable down to -15°C outside temperature, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, total-switch-off after 5min, OPH-counter with service information, optical flame monitoring with photoelectric cell and fault indicator-light) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, integrated diesel-tank 60l, separate space for 2 x 20l cleaning detergent-container c/w Remote activation, 2 different operating control level, 3 robust on-off push buttons for H.P. Pump, heating and detergent, 7,5m connection cable.

| | | |
|----------------|--------|--------|
| Art.No. | 527002 | 527001 |
|----------------|--------|--------|