


High Pressure Cleaner

HSC1140-INOX Gas



Type		HSC1140-INOX Gas
Voltage	3/N/PE/AC/50Hz/400V	<ul style="list-style-type: none"> Stainless steel (food safe) Etronic I - Controls 10m HP-Hose DN08 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle-Protection Stainless-Steel Jet-Nozzle 25° Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve
Operating pressure	30-165bar/3-16,5MPa	
Max. pressure	185bar/18,5MPa	
Discharge capacity	300-1000l/h	
Nozzle size	055	
Hot water capacity	30-70°C	
Pump speed	1400rpm	
Heating power	50kW	
Connected load	6,5kW/11,7A	
Electrical protection	3x16A slow	
Weight net/with package		313kg/330kg
Dimensions device/with package (LxWxH)		122x75,5x162,5cm/125x81,5x175,5cm

Self-supporting, robust, device-chassis made out of stainless-steel, suitable for floor installation, stainless-steel hotwater-boiler with 65l capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation, triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic I - controls: (start-stop system with switch-off delay, stand-by system for heating, OPH-counter with service information, low-water cut-off), unloader safety-valve c/w infinitely variable pressure and quantity regulation, separate space for 2x20l cleaning detergent-container c/w remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. Pump, heating and detergent, 7,5m connection cable.

Art.No. 52701