

High Pressure Cleaner

HSC840-INOX FR 24kW

NEW!



INOX



**Anti Freeze
circulatory system**

Type **HSC840-INOX FR 24kW**

Voltage	3/N/PE/AC/50Hz/400V	<ul style="list-style-type: none"> Suitable for winter operation down to -15°C outside temperature Antifreeze circulatory system with internal WAB Stainless steel lance quiver with anti-freeze water return to the WAB PLC to control the antifreeze circuit system with pressure relief Etronic I-Controls 10m HD-Hose DN08 - 315bar Shut-off pistol with low-pressure leakage Lance 900mm with nozzle protection Stainless steel flat jet nozzle 25° Water-Supply separation acc. DIN EN 1717 class 4 Chemical supply in high-pressure Jet c/w Metering-valve Recommendation: Installation Kit - Automatic Hose reel with 20m HP hose - optional
Operating pressure	30-130bar/3-13MPa	
Max. pressure	150bar/15MPa	
Discharge capacity	300-720l/h	
Nozzle size	045	
Heating capacity	24kW	
Hot water capacity	30-80°C	
Pump speed	1400rpm	
Connected load	28,8kW/44,2A	
Electrical protection	3x50A slow	
Weight net/with package		264kg/281kg
Dimensions device/with package (LxWxH)		122x75,5x162,5cm/125x81,5x175,5cm

Self-supporting, robust, device-chassis made out of stainless-steel, suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, thermostatically and SPS controlled frost protection circuit system with frost protection water recirculation in the internal WAB 40ltr, reliable down to -15°C outside temperature, stainless-steel hotwater-boiler with 65l capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation, triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic I - controls: (start-stop system with switch-off delay, stand-by system for heating, total-switch-off after 20min, OPH-counter with service information, low-water cut-off), unloader safety-valve c/w Infinitely variable pressure and quantity regulation, separate space for 2x20l cleaning detergent-container c/w remote activation, 2 different operating control level, 3 robust on-off push buttons for H.P. pump, heating and detergent, 7,5m connection cable.