


# High Pressure Cleaner

## HSC923 UK








**1400  
U/min**


**TSS**


**TOTAL  
STOP**











INOX

Type	HSC923 UK		HSC923 UK-INOX	
Voltage	1/N/PE/AC/50Hz/240V	<ul style="list-style-type: none"> <li>Etronic II - Controls</li> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>Stainless steel (food safe)</li> <li>Etronic II - Controls</li> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle-Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	
Operating pressure	30-100bar/3-10MPa			
Max. pressure	120bar/12MPa			
Discharge capacity	300-840l/h			
Nozzle size	070			
Hot water capacity	30-98°C			
Pump speed	1400rpm			
Connected load	3,3kW/13A			
Electrical protection	13A slow			
Weight net/with package				
Dimensions device/with package (LxWxH)		122x75,5x162,5cm/125x81,5x175,5cm	122x75,5x162,5cm/125x81,5x175,5cm	

Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), suitable for floor installation, 20mm PU-sound and thermal insulation, thermostatic chassis electric heating 80W, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (Start-stop system with switch-off delay, total-switch-off after 20min, OPH-counter with service information, optical flame monitoring with photoelectric cell and fault indicator-light) 2 motors system (independent of the direction of rotation) separately for H.P.-Pump and heating, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, integrated diesel-tank 60l, separate space for 2x20l cleaning detergent-container c/w Remote activation, 2 different operating control level, 3 robust on-off rotary switches for H.P. Pump, heating and detergent, 7,5m connection cable.

Art.No.	534001	534002
---------	--------	--------